

[illegible]

5 sub B.7

15

20

25

30

6-9 OK  
for  
29/898.06  
H Tan H.

press fitting a bearing assembly onto the  
trunion, the bearing assembly comprising an inner race,  
an outer race, and a plurality of rollers interposed  
therebetween to permit relative rotation between the  
5 inner and outer race; and  
axially retaining the bearing assembly to the  
spider.

7. A method according to claim 6, wherein the  
10 trunion is forged and the bearing is press-fit onto the  
trunion without machining the trunion.

8. A method according to claim 7, further  
comprising the step of angularly retaining the bearing to  
15 the trunion.

9. A method according to claim 8, further  
comprising the step of drawing the inner race.

20 *Sub B2* 10. A tripod bearing assembly including a  
spider, comprising:

a non-machined trunion radially provided on the  
spider, the trunion comprising an undercut adjacent the  
spider, a cylindrical surface, and a snap ring groove  
25 axially spaced from the undercut;

a bearing assembly press-fit onto the trunion  
between the spider and snap ring groove, the bearing  
assembly comprising an inner race, an outer race, and a  
plurality of needle rollers interposed therebetween to  
30 permit relative rotation between the inner and outer  
race; and

means for axially and angularly retaining the  
bearing assembly to the spider.

11. A bearing assembly according to claim 10,  
wherein the inner race comprises a formed cup.

12. A bearing assembly according to claim 11,  
5 wherein the cup is formed by drawing.

Add C<sub>2</sub> >  
Add O<sub>2</sub> >

08996249 132297